

CONTENTS

Your BEHNCKE team

Filling aid for filter material
made of V4A stainless steel

The new B400 Slim Skimmer

MATCHPOOLS MINI

Aquadeck® / New manufacturer

The digital BEHNCKE price list

Online training

Technical shaft



Your contact person ...


... external sales



Nicolas Christ

Export

T: +49 (0) 89 45 69 17-18
nicolas_christ@behncke.com



Angela Herrmann

International Sales Manager

M: +49 (0) 173 36 73 886
angela_herrmann@behncke.com

... technic



Martin Marschner

Head of technical customer support

martin_marschner@behncke.com



Philipp Brummer

Technical director


philipp_brummer@behncke.com



Thorsten Schäfer

Service - Engineer

thorsten_schaefer@behncke.com



Klaus Hammerschick

Service - Engineer

klaus_hammerschick@behncke.com

... PR / marketing



Katrin Riebel

Marketing Manager

T: +49 (0) 89 45 69 17-23
katrin_riebel@behncke.com



Filling aid for filter material made of V4A

Made of stainless steel for all filter² and filter³ models

The product is placed on the filter opening. It is provided with a tip that can tear open the AFM bag and thus the filter material trickles into the filter. This filling aid covers the sludge water funnel and protects the stud bolts from damage and dirt.



We recommend the filter material:
AFM from Dryden Aqua



Self-sanitizing surface:
Resistant to bacterial growth

Hydrophobic surface:
Filtered to 1 micron

Greatly enlarged surface:
For better adsorption and filtration



STAINLESS STEEL COMPONENTS



SLIM LINE Skimmer

We set standards in terms of water level and modern design

B400 Slim

NEW

Flow rate: 6 – 10 m³/h
Suction width: 335 mm



B500 Slim

Flow rate: 8 – 15 m³/h
Suction width: 460 mm



B600 Slim

Flow rate: 13 – 25 m³/h
Suction width: 665 mm



B500 Ultimate

Flow rate: 8 – 15 m³/h
Suction width: 460 mm



B600 Ultimate

Flow rate: 13 – 25 m³/h
Suction width: 665 mm



Guaranteed high water level
thanks to narrow mouth opening

Minimal water edge
due to missing upper flange edge



STAINLESS STEEL COMPONENTS

MATCHPOOLS MINI

Purchase. Let in. Dive in.

SMALL GARDEN - GREAT JOY.

Our MATCHPOOLS MINI concept fulfils the dream of your own dream pool.

www.matchpools.de

MATCHPOOLS MINI Stores



Poolsplace GmbH & Co. KG
Am Erlenpark 1, 77866 Rheinau, Germany
www.poolsplace.de



Scan QR code and discover more
Discover MATCHPOOLS MINI Stores
<https://matchpools.de/matchpools-mini-en/>

A project by:



MATCHPOOLS MINI

We enlarged to our existing product portfolio of the company **BAC** (Roller shutters, roll protection, foam covers) the segment around the company **Aquadeck®** Poolcovers.

Aquadeck® offers a variety of solutions for every pool. The cover defines the aesthetics of the pool. With an Aquadeck® pool cover you gain even more advantages:

- **Anti-algae system**
Avoid algae growth
- **100 % waterproof**
Ultrasonic welded
- **Solar slats**
Lowers the energy consumption for pool heating and extends your pool season
- **Design**
PVC or polycarbonate
- **Additional guarantee**
5 years warranty on devices and slats
- **Security**
A variety of safety precautions

Close _____
to be **perfect**

NEW PRODUCER

Digital price list

We move with times. All current data and prices available always.

Export Pricelist 2022
Swimming pool and heating technology.
Made in Germany.

Version 03/2022
The prices are valid from 15/04/2022

BEHNCKE GmbH

Everything about BEHNCKE ...

- Our new digital price list
- Our team in 60 seconds
- Our company in 60 seconds
- Image film
- Export film
- Location Munich
- Location Bühl

Administration, central sales, production site for stainless steel products, Maytronics Service Center.
BEHNCKE GmbH
Michael-Haibach-Str. 13
D-85640 Putzbrunn / Germany
Tel.: +49 (0) 89 456917-0
info@behncke.com
www.behncke.com

Production site for GRP-Filter
BEHNCKE GmbH
Sommering-Str. 54a
D-38835 Bülte / Germany

Our contact for you

This is how you work with our new price list

Swimming Pool Heat Exchanger "QWT 100"

2 combination sockets 1 1/2" x DN 40 or 2" x DN 50. For heating the swimming pool water by connecting to a central heating system. Consisting of stainless steel outer jacket with welded stainless steel pipe coil, complete with immersion sleeve to accommodate an electronic temperature sensor. Bracket and rubber hose mounting. Max. operating pressure: 10 bar on the heating side, 3 bar on the pool side.

Item	Output kW heat	Pump capacity heating m³/h	Pressure loss pool water m³/h	Pressure loss pool water kPa	Art. No.	GR	€ BPP w/o VAT
QWT 100-20	23	2	4,1	10	305 018 00	1	457,00
QWT 100-30	32	2	6,2	10	305 026 00	1	466,00
QWT 100-40	40	2	9,2	10	305 033 00	1	446,00
QWT 100-70	75	3	3,4	12	305 017 00	1	799,00
QWT 100-104	137	5	12,2	15	305 027 00	1	1.015,00
QWT 100-168	2 x 3	2 x 3,4	2 x 3,4	20	341 305 037 00	1	1.966,00
QWT 100-209	304	2 x 5	2 x 13,2	25	305 047 00	1	1.100,00

Unit conversion: 1 kW = 3,6 MJ/h

- Product name and explanatory text
- Product illustrations
- Product pictograms for easy assignment
- Table with item designations, technical data, item numbers and prices
- Goos with
- This is how you work with our new price list

GRP filter + systems for private pools

DRESDEN® filter tank

Made of glass fibre reinforced polyester resin. With large transparent service opening at the top (DN 800/900/1050/1200/1400/1600), with moulded-in lock with built-in filter cross, drain valve with hose connection, manometer and manual venting.

- According to DIN EN 12072
- Without valve set, with screwed connection
- Operating pressure max. 2,5 bar
- Operating temperature max. 40 °C
- Tank colour: RAL 7035 (light grey)

Surcharge for colour resistance 8 % of list price

Dimension D x Height mm	Service opening Ø mm	Value	Art. No.	GR	€ BPP w/o VAT
800 x 800	220 mm	429	708 400 02-19	3	249,00
900 x 900	300 mm	525	708 600 02-20	3	297,00
1000 x 1000	300 mm	525	708 600 02-20	3	336,00
1200 x 1200	300 mm	590	708 750 02-18	3	320,00
1400 x 1400	300 mm	625	708 500 02-16	5	327,00
1600 x 1600	300 mm	625	708 500 02-16	6	392,00
1800 x 1800	300 mm	625	708 500 02-16	8	430,00

Required filter material for filter tank DRESDEN®

for Ø	Grade 1 0.4-0.8 / bag	Grade 2 0.7-2.0 / bag	Total	Art. No.	GR	€ BPP w/o VAT
400	2	1	3	708 400 02-19	3	121,01
500	3	2	5	708 400 02-19	3	209,56
600	4	4	8	708 600 02-20	3	322,69
750	9	9	18	708 600 02-20	3	726,05

Our price list with lots of additional information

Discover now at: <https://behncke.1kcloud.com/ep16204d00d23376/#0>

- 24/7 access
- Daily updated prices and information
- The article number takes you directly to the online shop, where you can order immediately
- Many product videos, company videos and team presentations

Article number - With one click to the online shop

<https://www.behncke-onlineshop.com/>



DIGITAL PRICE LIST

BEHNCKE Pool School/Online training

Concentrated knowledge for our specialist dealers

You are a swimming pool retailer and want to know more around the topic of water treatment and swimming pool technology?

As a manufacturer of high-quality stainless steel components, swimming pool technology and with our aquavision® water treatment system, we are the right contact for you with our online training courses.

Register at marketing@behncke.com



Watch online training 2022 here

In Q1 2023 the next online training will take place

Our speakers:



Angela Herrmann
International Sales Manager



Martin Marschner
Head of technical customer support

Technology easily accommodated

Small and compact, everything under one roof.

The compact and high-quality equipped GRP technical shaft enables the quick and easy installation of the most important technical components for any type of mini pool up to a capacity of approx. 20 sqm. All components such as filter, pump, valve and measuring and control technology are supplied fully assembled. If a jet system is to be installed as an option, it can also be integrated into the technical shaft.

Technical shaft Smart 4



Technical shaft Smart 6 with DA-GEN



ONLINE TRAINING & TECHNICAL SHAFT